



# P329*S*

with *W*ireless Technology

## 3 in 1

Touch Screen Operated  
Battery Powered  
Plastic Strapping Tool



for HD Applications  
with Strap Widths from  
16 ( $\frac{5}{8}$ " ) up to 19 mm ( $\frac{3}{4}$ " )  
and a Tension Force up to 4.000 N/900 lbs.





## P329S, with Wireless Technology.

### 3 in 1 Touch Screen Operated, Battery Powered Plastic Strapping Tool for HD applications

The P329S strapping tool is equipped with an easy to operate colour touch screen, located always in-sight of the operator. Clear to read symbols make that everybody can work Smart with it.

This unique 3 in 1 tool combines Manual, Semi-Automatic or Automatic operation in one tool, by simply selecting the mode you want to use. Without changing the tool.

No more mechanical buttons. The slanted placed touch screen, with its flat outlet at the bottom, prevents water and dust from entering the device here, extending service life dramatically .

Consistent and reliable performance - with teach-in mode - by easy setting and locking of the right tension force, speed and sealing time at the touch of a finger. This one-handed operation tool allows you to consistently strap a great variety of products, in series or individual and variable packages.

Tested to endure, the P329S has passed several severe quality endurance tests to meet and exceed the demanding FROMM quality requirements and customer demand.

*If equipped with Wireless Technology, the P329S offers extra features in programming, updating and service readout.*

**Ask your FROMM representative for a demonstration!**

#### Main characteristics

Strapping qualities:

Strapping dimensions:

Weight:

Dimensions with 4.0 Ah battery:

Average seal strength:

Tension force:

Tensioning speed:

Power supply:

widths  
thicknesses

#### P329S

PET plain and embossed

16.0 - 19.0 mm / 5/8 - 3/4"

0.65 - 1.35 mm / .026 - .053"

4.3 kg / 9.6 lbs (including 4.0 Ah battery)

L351 x W134 x H143 mm / 13.8 x 5.3 x 5.6"

approx. 75 % (dependent on strap quality)

500 - 4.000 N / 112 - 900 lbs (adjustable in steps of 5%)

32 - 113 mm/s / 1.3 - 4.5 inch/s

Battery 18 VDC / 4.0 Ah or 9.0 Ah Li-Ion

### More Smart Features & Benefits that really matter to you

- Performance tested, your guarantee for a problem free, long-life operation:
  - \*The Touch Screen surpassed the FET2017-1 300.000 cycle endurance test, under the most severe and abrasive conditions as well as the FST2017-2 Ball-Drop-Test to resist impacts from outside;
  - \*The complete tool was subjected to the FROMM durability test with > 300.000 seals, the FCT2016-4 Vibration test and the LT2018/1 Temperature test.
- Work with a mix of strap types. No resetting. Simply select one of the pre-stored strap types, or use 1 of the 10 free programmable profiles;
- Durable till the end. Designed to easy operate and maintain, based on sustainable techniques and materials. Easy-to-Recycle, separating plastics, metals and other products;
- FROMM re-confirms the quality of its products with a 24 months manufacturer's warranty period;
- AlwaysGood strap alinement and optimal seal efficiency by means of double strap guides;
- Easy inserting and removing the strap, no obstacles from hands or other barriers;
- Well balanced tool. For strapping in various positions with extra finger protection;
- Well protected sturdy battery mount for 4.0 or 9.0Ah battery with charge indicator;
- Improved life cycle by brushless motor with motor temperature monitoring system. Protecting the motor from overheating under the most harsh conditions. Optional motor cooling fan available for extreme environments;
- Easy cleaning results in long service life of up to 80.000 straps. The maintenance info system will tell you when service is advised;
- High, consistent and easy to control tension force up to 4.000 N / 900 lbs.



Two button Semi-Automatic Mode



One button Automatic Mode

[www.fromm-pack.com](http://www.fromm-pack.com)